

Filter type	<b>DUO-UV</b>
Connection diameter	3/4" and 1"
Recommended flow (m³/h) at 25 mJ/cm²	1,7
Recommended flow (m³/h) at 40 mJ/cm²	1,1
Operating pressure (bar)	10
Max. working pressure (bar)	16
Max. temperature (°C)	50
Weight (kg)	3,05 / 4,70 (with packaging)
Packaging in mm	521x466x141
Filter head	PP GF
Bowls	SAN (transparente) and PP GF
Wrench	PP GF
Bowl seals	O-ring NBR + Viton
Centrifugal impeller + cover	HDPE
Drain screw	PA GF
UV drain screw	PVDF
Sieve support	PP GF
Filter sieve	Polyester (Non-washable) or nylon (Washable)
Filtration area	440 cm² avec tamis
UV-C lamp	25W avec safandy micro-switch
UV treatment chamber	Inox 316 L
Equipement d'origine	Tamis filtrant 25 µm, 1 lampe UV-C 25W, 1 clé, 1 fixation murale inox + 1 fixation PP GF + 2 raccords 3/4" + 2 raccords 1" + indicateur de temps 12mois <22°C
Options	<i>Non lavable</i> : 1 - 5 - 10 - 25 - 50 - 100
Autres finesses disponibles (µm)	<i>Lavable</i> : 150 - 300
(set de 5 tamis)	

