

Filter type	NW25 DUO-CTN
Connection diameter	¾ · and 1·
Average flow rate (m³/h)	2,5 at delta-P 0,8 bar
Operating pressure (bar)	10
Max. working pressure (bar)	16
Max. temperature (°C)	50
Weight (kg)	3,2 / 3,7 (with packaging)
Packaging in mm (L x W x D)	370x325x126
Filter head	PP GF
Bowl	SAN
Wrench	PP GF
Seals	O-ring NBR
Centrifugal impeller + cover	HDPE
Drain screw	PA GF
Sieve support	PP GF
Filter sieve	Polyester (Non-washable) ornylon (Washable)
CTN cartridge for AC	SAN (corps) 600µm+ PP GF (covercle) 300µm
Filtration area / volume	440 cm² avec tamis + 0,57 L charbon actif
Standard equipment	Tamisfiltrant 25 µm, CTN remplie avec charbon actif, 1 wrench, 2 fixations murales en PP GF + 2 fittings ¾· + 2 fittings 1·
Options	vanne à bille ¼· · laiton nickelé, pressure gauges 1/8· · laiton
Other available mesh sizes (µm) (set de 5 tamis)	Non-washable : 1 - 5 - 10 - 25 - 50 - 100 Lavable : 150 - 300

