



|  |  |
|--|--|
| Filter type  | <b>SL240 DUO-CTN</b>   |
| Connection diameter                                  | ¾ · or 1 ·   |
| Average flow rate (m³/h)                             | 1,8at delta-P 0,8 bar  |
| Operating pressure (bar)                             | 8  |
| Max. working pressure (bar)                          | 12   |
| Max. temperature (°C)                                | 50   |
| Weight (kg)  | 1,85 / 2,37 (with packaging)   |
| Packaging in mm                                      | 328x265x120  |
| Filter head  | PP   |
| Bowl   | SAN  |
| Wrench   | PP GF  |
| Sieve support  | PP GF  |
| Seals  | O-ring NBR   |
| Centrifugal impeller + cover                         | HDPE   |
| Filter sieve   | Polyester (Non-washable) or nylon (Washable)   |
| Filtration area + volume                             | 440 cm² avec tamis + 0,57L avec charbon actif  |
| CTN cartridge for AC                                 | SAN (corps) 600µm+ PP GF (covercle) 300µm  |
| Standard equipment                                   | Tamis filtrant 25 µm, CTN remplie avec charbon actif, wrench, 2 fixations murales en PP GF |
| Other available mesh sizes (µm)<br>(set of 5 sieves) | Non-washable : 1 -5-10-25-50-100<br>Washable: 150-300                                      |

