


Filter type	TRIO-UV 6100 (60W)	
Connection diameter	1"	
Recommended flow (m³/h) at 25 mJ/cm²	5.34	
Recommended flow (m³/h) at 40 mJ/cm²	3.34	
Operating pressure (bar)	10	
Max. working pressure (bar)	16	
Max. temperature (°C)	50	
Weight (kg)	10,7 / 13,5 (avec emballage)	
Packaging in mm	800 x 410 x 595	
Filter head	Polypropylène (PP) + 20% GF	
Bowls	Pand	
Black bowl	Polypropylène (PP) + 20% GF coloré	
Wrench	ABS	
Bowl seals	O-ring butadiene-acrylonitrile (NBR)	
Centrifugal impeller + cover	Polypropylène (PP) + 20% GF	
Drain screw	Polyamide (PA) + 40% GF	
UV drain screw	PVDF	
Sieve support	Polypropylène (PP) + 20% GF	
Filter sieve	Polyester (Non-washable) ornylon (Washable)	
CTN cartridge for AC	SAN (corps) 0,6mm + PP GF (corvercle) 0,3mm	
Filtration area / volume	530 cm² avec tamis + 0,75 L charbon actif	
UV-C lamp	60W avec safandy micro-switch	
UV treatment chamber	Inox 316 L	
Equipement d'origine	Tamis filtrant 25 µm, CTN avec charbon actif, 1 ballast sans affichage, 1 lampe UV-C 60W, 1 time label 24 mois, 1 clé, 3 fixations murales inox, 3 vannes de purge ½", 2 raccords 1" , 2 manomètres 1/4"	
Autres finesses disponibles (µm) (set de 5 tamis)	<i>Non lavable</i> : 1 - 5 - 10 - 25 - 50 - 100 <i>Lavable</i> : 50 - 90 - 150 - 300	

